

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form	: Substance
Substance name	: Xylenes
CAS No	: 1330-20-7
Product code	: VT910
Formula	: C8H10
Synonyms	: benzene, dimethyl- / dimethylbenzene, mixture of isomers / dimethylbenzol, mixture of isomers / methyltoluene, mixture of isomers / mixed xylenes / xylol
Other means of identification	: Xylenes, mixture of ortho, meta and para isomers with ethylbenzene

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture	: Solvent Cleaning product Chemical raw material
------------------------------	--

#### 1.3. Details of the supplier of the safety data sheet

Val Tech Diagnostics, A Division of LabChem Inc  
 Jackson's Pointe Commerce Park Building 1000  
 1010 Jackson's Pointe Court  
 Zelienople, PA 16063  
 T 412-826-5230  
 F 724-473-0647

#### 1.4. Emergency telephone number

Emergency number : CHEMTREC: 1-800-424-9300 or 011-703-527-3887

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification (GHS-US)

Flam. Liq. 3 H226  
 Skin Irrit. 2 H315  
 Aquatic Acute 2 H401

Full text of H-phrases: see section 16

#### 2.2. Label elements

##### GHS-US labeling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) :

Warning

Hazard statements (GHS-US) :

H226 - Flammable liquid and vapor  
 H315 - Causes skin irritation  
 H401 - Toxic to aquatic life

Precautionary statements (GHS-US) :

P210 - Keep away from heat, hot surfaces, open flames, sparks. - No smoking  
 P233 - Keep container tightly closed  
 P240 - Ground/bond container and receiving equipment  
 P241 - Use explosion-proof electrical, lighting, ventilating equipment  
 P242 - Use only non-sparking tools  
 P243 - Take precautionary measures against static discharge  
 P264 - Wash exposed skin thoroughly after handling  
 P273 - Avoid release to the environment  
 P280 - Wear eye protection, face protection, protective clothing, protective gloves  
 P303+P361+P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower  
 P332+P313 - If skin irritation occurs: Get medical advice/attention

# Xylenes

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P363 - Wash contaminated clothing before reuse  
P370+P378 - In case of fire: Use carbon dioxide (CO<sub>2</sub>), powder, alcohol-resistant foam to extinguish  
P403+P235 - Store in a well-ventilated place. Keep cool  
P501 - Dispose of contents/container to comply with local, state and federal regulations

### 2.3. Other hazards

Other hazards not contributing to the classification : None.

### 2.4. Unknown acute toxicity (GHS-US)

No data available

## SECTION 3: Composition/information on ingredients

### 3.1. Substance

Substance type : Multi-constituent  
Name : Xylenes  
CAS No : 1330-20-7  
EC no : 215-535-7  
EC index no : 601-022-00-9

Name	Product identifier	%	Classification (GHS-US)
Xylenes (Main constituent)	(CAS No) 1330-20-7	100	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Aquatic Acute 2, H401

Full text of H-phrases: see section 16

### 3.2. Mixture

Not applicable

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general : Check the vital functions. Unconscious: maintain adequate airway and respiration. Respiratory arrest: artificial respiration or oxygen. Cardiac arrest: perform resuscitation. Victim conscious with labored breathing: half-seated. Victim in shock: on his back with legs slightly raised. Vomiting: prevent asphyxia/aspiration pneumonia. Prevent cooling by covering the victim (no warming up). Keep watching the victim. Give psychological aid. Keep the victim calm, avoid physical strain. Depending on the victim's condition: doctor/hospital. Never give alcohol to drink.

First-aid measures after inhalation : Remove the victim into fresh air. Respiratory problems: consult a doctor/medical service.

First-aid measures after skin contact : Wash immediately with lots of water. Soap may be used. Do not apply (chemical) neutralizing agents. Take victim to a doctor if irritation persists.

First-aid measures after eye contact : Rinse immediately with plenty of water. Do not apply neutralizing agents. Take victim to an ophthalmologist if irritation persists.

First-aid measures after ingestion : Rinse mouth with water. Do not induce vomiting. Call Poison Information Centre ([www.big.be/antigif.htm](http://www.big.be/antigif.htm)). Consult a doctor/medical service if you feel unwell. Ingestion of large quantities: immediately to hospital.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation : EXPOSURE TO HIGH CONCENTRATIONS: Irritation of the respiratory tract. Irritation of the nasal mucous membranes. Central nervous system depression. Dizziness. Headache. Coordination disorders. Disturbed motor response. Impaired memory. Disturbances of consciousness.

Symptoms/injuries after skin contact : Tingling/irritation of the skin.

Symptoms/injuries after eye contact : Irritation of the eye tissue.

Symptoms/injuries after ingestion : AFTER ABSORPTION OF LARGE QUANTITIES: Enlargement/disease of the liver. Symptoms similar to those listed under inhalation.

Chronic symptoms : ON CONTINUOUS/REPEATED EXPOSURE/CONTACT: Dry skin. Itching.

### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

# Xylenes

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

- Suitable extinguishing media : Water spray. Polyvalent foam. Alcohol-resistant foam. BC powder. Carbon dioxide.
- Unsuitable extinguishing media : Solid water jet ineffective as extinguishing medium.

#### 5.2. Special hazards arising from the substance or mixture

- Fire hazard : DIRECT FIRE HAZARD. Flammable. Gas/vapor flammable with air within explosion limits. INDIRECT FIRE HAZARD. May build up electrostatic charges: risk of ignition. May be ignited by sparks. Gas/vapor spreads at floor level: ignition hazard. Reactions involving a fire hazard: see "Reactivity Hazard".
- Explosion hazard : DIRECT EXPLOSION HAZARD. Gas/vapour explosive with air within explosion limits. INDIRECT EXPLOSION HAZARD. may be ignited by sparks. Reactions with explosion hazards: see "Reactivity Hazard".
- Reactivity : Upon combustion: CO and CO<sub>2</sub> are formed. Reacts violently with (strong) oxidizers: (increased) risk of fire/explosion. Reacts with (some) acids.

#### 5.3. Advice for firefighters

- Precautionary measures fire : Exposure to fire/heat: keep upwind. Exposure to fire/heat: consider evacuation. Exposure to fire/heat: seal off low-lying areas. Exposure to fire/heat: have neighbourhood close doors and windows.
- Firefighting instructions : Cool tanks/drums with water spray/remove them into safety.
- Protection during firefighting : Heat/fire exposure: compressed air/oxygen apparatus.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### 6.1.1. For non-emergency personnel

- Protective equipment : Gloves. Face-shield. Protective clothing. Large spills/in enclosed spaces: compressed air apparatus. See "Material-Handling" to select protective clothing.
- Emergency procedures : Mark the danger area. Stop engines and no smoking. No naked flames or sparks. Spark- and explosion-proof appliances and lighting equipment. Wash contaminated clothes. Large spills/in confined spaces: consider evacuation. In case of reactivity hazard: consider evacuation.

##### 6.1.2. For emergency responders

- Protective equipment : Equip cleanup crew with proper protection. Do not breathe gas, fumes, vapor or spray.
- Emergency procedures : If a major spill occurs, all personnel should be immediately evacuated and the area ventilated. Stop release. Ventilate area.

#### 6.2. Environmental precautions

- Prevent spreading in sewers.

#### 6.3. Methods and material for containment and cleaning up

- For containment : Contain released substance, pump into suitable containers. Plug the leak, cut off the supply. Dam up the liquid spill. Provide equipment/receptacles with earthing. Do not use compressed air for pumping over spills. Heating: dilute combustible gas/vapour with water curtain.
- Methods for cleaning up : Take up liquid spill into a non combustible material e.g.: sand, earth, vermiculite or powdered limestone. Scoop absorbed substance into closing containers. Carefully collect the spill/leftovers. Spill must not return in its original container. Damaged/cooled tanks must be emptied. Do not use compressed air for pumping over spills. Clean contaminated surfaces with an excess of water. Take collected spill to manufacturer/competent authority. Wash clothing and equipment after handling.

#### 6.4. Reference to other sections

- No additional information available

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

- Precautions for safe handling : Comply with the legal requirements. Remove contaminated clothing immediately. Clean contaminated clothing. Thoroughly clean/dry the installation before use. Do not discharge the waste into the drain. Do not use compressed air for pumping over. Use spark-/explosionproof appliances and lighting system. Take precautions against electrostatic charges. Keep away from naked flames/heat. Keep away from ignition sources/sparks. Observe normal hygiene standards. Keep container tightly closed. Measure the concentration in the air regularly. Carry operations in the open/under local exhaust/ventilation or with respiratory protection.

# Xylenes

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product.  
Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

### 7.2. Conditions for safe storage, including any incompatibilities

Incompatible products : Strong oxidizers.  
Heat-ignition : KEEP SUBSTANCE AWAY FROM: heat sources. ignition sources.  
Prohibitions on mixed storage : KEEP SUBSTANCE AWAY FROM: combustible materials. oxidizing agents. strong acids. halogens. highly flammable materials.  
Storage area : Store in a cool area. Ventilation at floor level. Fireproof storeroom. Provide for a tub to collect spills. Provide the tank with earthing. Meet the legal requirements.  
Special rules on packaging : SPECIAL REQUIREMENTS: closing. clean. correctly labelled. meet the legal requirements. Secure fragile packagings in solid containers.  
Packaging materials : SUITABLE MATERIAL: No data available. MATERIAL TO AVOID: No data available.

### 7.3. Specific end use(s)

No additional information available

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

Xylenes (1330-20-7)		
USA ACGIH	ACGIH TWA (ppm)	100 ppm
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	435 mg/m <sup>3</sup>
USA OSHA	OSHA PEL (TWA) (ppm)	100 ppm

### 8.2. Exposure controls

Appropriate engineering controls : Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Provide adequate general and local exhaust ventilation.  
Materials for protective clothing : GIVE EXCELLENT RESISTANCE: No data available. GIVE GOOD RESISTANCE: PVA. viton. tetrafluoroethylene. GIVE LESS RESISTANCE: No data available. GIVE POOR RESISTANCE: butyl rubber. natural rubber. neoprene. polyethylene. nitrile rubber.  
Hand protection : Gloves.  
Eye protection : Face shield.  
Skin and body protection : Protective clothing.  
Respiratory protection : Wear gas mask with filter type A if conc. in air > exposure limit.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state : Liquid  
Appearance : Liquid.  
Molecular mass : 106.17 g/mol  
Color : Colourless to light yellow.  
Odor : Pleasant odour. Aromatic odour.  
Odor threshold : No data available  
pH : No data available  
Relative evaporation rate (butyl acetate=1) : No data available  
Relative evaporation rate (ether=1) : 9.2 - 13.5  
Melting point : No data available  
Freezing point : No data available  
Boiling point : 135 - 145 °C  
Flash point : 25 °C  
Critical temperature : 346 - 359 °C  
Auto-ignition temperature : 464 °C  
Decomposition temperature : No data available  
Flammability (solid, gas) : No data available  
Vapor pressure : 6.7 - 8.7 hPa  
Vapor pressure at 50 °C : 32 - 43 hPa

# Xylenes

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Critical pressure	: 35160 - 37100 hPa
Relative vapor density at 20 °C	: 3.7
Relative density	: 0.86 - 0.88
Relative density of saturated gas/air mixture	: 1.02
Specific gravity / density	: 861 - 880 kg/m <sup>3</sup>
Solubility	: Insoluble in water. Soluble in ethanol. Soluble in ether. Soluble in acetone. Soluble in petroleum spirit. Water: < 0.02 g/100ml Ethanol: Complete Ether: Complete
Log Pow	: 3.2 (Conclusion by analogy; 20 °C)
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Explosive limits	: 1.0 - 7.0 vol % 44 - 310 g/m <sup>3</sup>

### 9.2. Other information

Minimum ignition energy	: 0.2 mJ
Specific conductivity	: 0.1 pS/m
Saturation concentration	: (20°C) 29/37
VOC content	: 100 %
Other properties	: Gas/vapour heavier than air at 20°C. Clear. Physical properties depending on the composition. Slightly volatile. May generate electrostatic charges.

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Upon combustion: CO and CO<sub>2</sub> are formed. Reacts violently with (strong) oxidizers: (increased) risk of fire/explosion. Reacts with (some) acids.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No additional information available

### 10.4. Conditions to avoid

High temperature. Incompatible materials. Open flame. Sparks.

### 10.5. Incompatible materials

Strong oxidizers. Strong acids.

### 10.6. Hazardous decomposition products

Carbon dioxide. Carbon monoxide.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : Not classified

Xylenes ( f )1330-20-7	
LD50 oral rat	3523 - 8600 mg/kg (Rat; OECD 401: Acute Oral Toxicity; Literature study; 3523 mg/kg bodyweight; Rat; OECD 401: Acute Oral Toxicity; Experimental value; >4000 mg/kg bodyweight; Rat; OECD 401: Acute Oral Toxicity; Experimental value)
LD50 dermal rabbit	> 4200 mg/kg body weight (Rabbit; Experimental value; OECD 402: Acute Dermal Toxicity)
LC50 inhalation rat (mg/l)	29 mg/l/4h (Rat; Experimental value; 27.57 mg/l/4h; Rat; Experimental value)

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified

# Xylenes

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Carcinogenicity : Not classified

### Xylenes (1330-20-7)

IARC group	3 - Not classifiable
Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: Not classified
Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: Not classified
Symptoms/injuries after inhalation	: EXPOSURE TO HIGH CONCENTRATIONS: Irritation of the respiratory tract. Irritation of the nasal mucous membranes. Central nervous system depression. Dizziness. Headache. Coordination disorders. Disturbed motor response. Impaired memory. Disturbances of consciousness.
Symptoms/injuries after skin contact	: Tingling/irritation of the skin.
Symptoms/injuries after eye contact	: Irritation of the eye tissue.
Symptoms/injuries after ingestion	: AFTER ABSORPTION OF LARGE QUANTITIES: Enlargement/disease of the liver. Symptoms similar to those listed under inhalation.
Chronic symptoms	: ON CONTINUOUS/REPEATED EXPOSURE/CONTACT: Dry skin. Itching.

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general	: Not classified as dangerous for the environment according to the criteria of Regulation (EC) No 1272/2008. Not classified as dangerous for the environment according to the criteria of Directive 67/548/EEC.
Ecology - air	: Not classified as dangerous for the ozone layer (Regulation (EC) No 1005/2009). Not included in the list of substances which may contribute to the greenhouse effect (Regulation (EC) No 842/2006). TA-Luft Klasse 5.2.5/I.
Ecology - water	: Fouling to shoreline. Ground water pollutant. Toxic to fishes. Toxic to invertebrates (Daphnia). Toxic to algae. Not harmful to activated sludge.

### Xylenes (1330-20-7)

LC50 fish 1	13.5 mg/l (96 h; <i>Lepomis macrochirus</i> ; Lethal)
EC50 Daphnia 1	150 mg/l (24 h; <i>Daphnia magna</i> )
LC50 fish 2	3.77 mg/l 96 h; <i>Salmo gairdneri</i> ( <i>Oncorhynchus mykiss</i> )
EC50 Daphnia 2	7.4 mg/l (48 h; <i>Daphnia magna</i> )
Threshold limit algae 1	72 mg/l (336 h; <i>Selenastrum capricornutum</i> ; Growth)
Threshold limit algae 2	10 mg/l (72 h; <i>Skeletonema costatum</i> )

### 12.2. Persistence and degradability

#### Xylenes (1330-20-7)

Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. No test data on mobility of the substance available. Photolysis in the air.
-------------------------------	--

### 12.3. Bioaccumulative potential

#### Xylenes (1330-20-7)

BCF fish 1	15 8 weeks; <i>Salmo gairdneri</i> ( <i>Oncorhynchus mykiss</i> )
BCF fish 2	7 - 26 (8 weeks; <i>Oncorhynchus mykiss</i> )
Log Pow	3.2 (Conclusion by analogy; 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

### 12.4. Mobility in soil

#### Xylenes (1330-20-7)

Ecology - soil	May be harmful to plant growth, blooming and fruit formation.
----------------	---

### 12.5. Other adverse effects

No additional information available

# Xylenes

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

- Waste disposal recommendations : Remove waste in accordance with local and/or national regulations. Hazardous waste shall not be mixed together with other waste. Different types of hazardous waste shall not be mixed together if this may entail a risk of pollution or create problems for the further management of the waste. Hazardous waste shall be managed responsibly. All entities that store, transport or handle hazardous waste shall take the necessary measures to prevent risks of pollution or damage to people or animals. Recycle by distillation. Incinerate under surveillance with energy recovery. Do not discharge into surface water.
- Additional information : LWCA (the Netherlands): KGA category 03. Hazardous waste according to Directive 2008/98/EC.

### SECTION 14: Transport information

- In accordance with DOT
- Transport document description : UN1307 Xylenes, 3, III
- UN-No.(DOT) : 1307
- DOT NA no. : UN1307
- Proper Shipping Name (DOT) : Xylenes
- Department of Transportation (DOT) Hazard Classes : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120
- Hazard labels (DOT) : 3 - Flammable liquid



- Packing group (DOT) : III - Minor Danger
- DOT Special Provisions (49 CFR 172.102) : B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has a flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this subchapter are applicable.  
IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672).  
T2 - 1.5 178.274(d)(2) Normal..... 178.275(d)(3)  
TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling =  $97 / 1 + a (tr - tf)$  Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.
- DOT Packaging Exceptions (49 CFR 173.xxx) : 150
- DOT Packaging Non Bulk (49 CFR 173.xxx) : 203
- DOT Packaging Bulk (49 CFR 173.xxx) : 242
- DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 60 L
- DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 220 L
- DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.

#### Additional information

- Other information : No supplementary information available.

#### ADR

- Transport document description : UN 1307, 3, III, (D/E)
- Packing group (ADR) : III
- Class (ADR) : 3 - Flammable liquid
- Hazard identification number (Kemler No.) : 30
- Classification code (ADR) : F1

# Xylenes

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hazard labels (ADR) : 3 - Flammable liquids



Orange plates :



Tunnel restriction code : D/E

### Transport by sea

UN-No. (IMDG) : 1307  
Class (IMDG) : 3 - Flammable liquids  
EmS-No. (1) : F-E  
EmS-No. (2) : S-D

### Air transport

UN-No.(IATA) : 1307  
Class (IATA) : 3 - Flammable Liquids  
Packing group (IATA) : III - Minor Danger

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

#### Xylenes (1330-20-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory  
Listed on United States SARA Section 313

RQ (Reportable quantity, section 304 of EPA's List of Lists) 100 lb

SARA Section 311/312 Hazard Classes Fire hazard

### 15.2. International regulations

#### CANADA

#### Xylenes (1330-20-7)

WHMIS Classification Class B Division 2 - Flammable Liquid  
Class D Division 2 Subdivision B - Toxic material causing other toxic effects

### EU-Regulations

No additional information available

### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flam. Liq. 3 H226  
Acute Tox. 4 (Inhalation) H332  
Acute Tox. 4 (Dermal) H312  
Skin Irrit. 2 H315

Full text of H-phrases: see section 16

### Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

R10  
Xn; R20/21  
Xi; R38

Full text of R-phrases: see section 16

### 15.2.2. National regulations

No additional information available



# Xylenes

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 15.3. US State regulations

#### Xylenes(1330-20-7)

U.S. - California - Proposition 65 - Carcinogens List	No
U.S. - California - Proposition 65 - Developmental Toxicity	No
U.S. - California - Proposition 65 - Reproductive Toxicity - Female	No
U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No

### SECTION 16: Other information

Full text of H-phrases: see section 16:

Aquatic Acute 2	Hazardous to the aquatic environment - Acute Hazard Category 2
Flam. Liq. 3	Flammable liquids Category 3
Skin Irrit. 2	Skin corrosion/irritation Category 2
H226	Flammable liquid and vapor
H315	Causes skin irritation
H401	Toxic to aquatic life

NFPA health hazard


: 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.

NFPA fire hazard

: 3 - Liquids and solids that can be ignited under almost all ambient conditions.

NFPA reactivity

: 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



#### HMIS III Rating

Health : 2 Moderate Hazard - Temporary or minor injury may occur

Flammability : 3 Serious Hazard

Physical : 0 Minimal Hazard

Personal Protection : H

SDS US ValTech

*Information in this SDS is from available published sources and is believed to be accurate. No warranty, express or implied, is made and LabChem Inc assumes no liability resulting from the use of this SDS. The user must determine suitability of this information for his application.*